

SZL-WLA-A-LL3

(Home : Products : Sw itches : MICRO SWITCH™ Limit Sw itches : MICRO SWITCH™ Global Limit Sw itches : SZL-WL)



General Purpose Lim it Switch, Series WL; Side Rotary; Single Pole Double Throw ,Double Break; Overtravel; Weld-imm une; LED lam p(DC24V)

Actual product appearance may vary.

Product Specifications

Availability	Asia-Pacific
Operating Force (OF)	9,8 N [2.22 lb] max.
Release Force	0,98 N [0.22 lb] min.
Pretravel (PT)	14° to 22°
Overtravel (OT)	55° min.
Differential Travel (DT)	12° max.
Product Type	General Purpose Limit Sw itch
Actuator	Side Rotary - Roller Lever Standard
Lever Type	Roller - Standard
Circuitry	SPDT-DB (1 CKT DB)
Ampere Rating	6 A 24 Vdc
Supply Voltage	24 Vdc max.
Housing Material	Aluminum Die-Cast
Termination Type	PF1/2
Series Name	SZL-WL
Shock	30 g max.
Vibration	10 Hz to 50 Hz at double amplitude of 1,5 mm
Sealing	IP67
UL File #	E150950
Expected Mechanical Life	15 Million
Operating Temperature	-10 °C to 80 °C [14 °F to 176 °F]
Comment	LED lamp(dc 24V)
Agency Approvals and Standards	UL, CE, CSA
UNSPSC Code	39122213
UNSPSC Commodity	39122213 Limit Sw itches
Sealed	Industrial