

**SZL-WLC-B**

( Home : Products : Sw itches : MICRO SWITCH™ Limit Sw itches : MICRO SWITCH™ Global Limit Sw itches : SZL-WL )



**General Purpose Lim it Switch, Series WL; Side Rotary - Adjustable; Single Pole Double Throw,Double Break; Overtravel**

Actual product appearance may vary.

**Product Specifications**

Availability	Asia-Pacific
Operating Force (OF)	8,82 N [1.98 lb] max.
Release Force	0,49 N [0.11 lb] min.
Pretravel (PT)	25° to 30°
Overtravel (OT)	60° min.
Differential Travel (DT)	16° max.
Product Type	General Purpose Limit Sw itch
Actuator	Side Rotary - Roller Lever Adjustable
Lever Type	Roller - Adjustable
Circuitry	SPDT-DB (1 CKT DB)
Ampere Rating	10 A 125/250 Vac, 0.8 A 125 Vdc
Supply Voltage	480 Vac/250 Vdc max.
Housing Material	Aluminum Die-Cast
Termination Type	PF1/2
Series Name	SZL-WL
Shock	30 g max.
Vibration	10 Hz to 50 Hz at double amplitude of 1,5 mm
Sealing	IP67
UL File #	E150950
Expected Mechanical Life	15 Million
Operating Temperature	-10 °C to 80 °C [14 °F to 176 °F]
Agency Approvals and Standards	UL, CE, CSA
UNSPSC Code	39122213
UNSPSC Commodity	39122213 Limit Sw itches
Sealed	Industrial

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Honeywell:](#)

[SZL-WLC-B](#)